



CUSHMAN®

# HAULER® PRO



## NO JOB OUT OF RANGE. NO TASK OFF LIMITS.

With its remarkable 50-mile range and quiet 72-volt AC powertrain, the Hauler® PRO has the stamina few gas vehicles can match. Impressive energy efficiency, low operational cost and standard features that include a 12-cubic foot cargo bed with a 800-lb load capacity, a brush guard, an E-Shield™ frame, and a rear hitch receiver give you the flexibility to go farther and accomplish more. Go pro with the Commercial Package upgrade to add 20-inch tires, brakelights, USB outlet, and more. Optional four-wheel hydraulic brakes give you more stopping power.

**LET'S WORK.®**

**72V**  
AC  
ELECTRIC

**1500LB**  
TOW  
CAPACITY

**50 MILES**  
PER BATTERY  
CHARGE

**1200LB**  
LOAD  
CAPACITY



# CUSHMAN® HAULER® PRO



STANDARD BRUSH GUARD



CARGO NET



VERSATILE DASH STORAGE



OPTIONAL ELECTRIC BED LIFT

## OPTIONS & ACCESSORIES

- Bed Dividers
- Long-Handled Tool Holder
- Cargo Mesh Netting
- L-Track Aluminum Bed System
- Weather Enclosure
- USB Outlet\*
- 12-Volt Outlet
- Canopy Storage Net
- Brush Guard\*
- Rearview Mirror
- ROPS-Certified Cab
- Ladder/Hoop Rack
- Brake Lights\*
- Tail Lights\*
- 20" Improved surface tires\*
- Large Fender Flare\*
- E-Shield™ Frame\*
- Premium Steering Wheel\*

\*Included in Commercial Package



COVERED WITH THE 2-YEAR CUSHMAN CARE TOTAL PROTECTION WARRANTY

### BODY & CHASSIS

FRAME	Welded Steel with DuraShield™ Powder Coat
BODY & FINISH	Injection Molded TPO
STANDARD COLOR	Patriot Blue

### DIMENSIONS

OVERALL LENGTH	115 in (292.1 cm)
OVERALL WIDTH	49.4 in (125.5 cm)
OVERALL HEIGHT W/CANOPY	70.5 in (179.1 cm)
WHEEL BASE	76 in (193 cm)
FRONT WHEEL TRACK	35 in (88.9 cm)
REAR WHEEL TRACK	38.5 in (97.8 cm)
GROUND CLEARANCE	4.5 in (11.4 cm)
CARGO BOX CAPACITY	12 cu ft (0.34 m <sup>3</sup> )

### POWER

POWER SOURCE	72-Volts
MOTOR TYPE	AC Induction
HORSEPOWER (KW)	22.4HP (16.7 kW) - Measured at Peak Torque
ELECTRICAL SYSTEM	72 Volt
BATTERY (QTY/TYP)	Nine 8-Volt Deep Cycle
BATTERY CHARGER	900 Watt 72V DC
KEY OR PEDAL START	Pedal
DRIVE TRAIN	Motor Shaft Direct Drive
TRANSAXLE	Differential with Helical Gears
SPEED CONTROLLER	350 Amp AC
GEAR SELECTION	Forward-Neutral-Reverse
REAR AXLE RATIO	17:1

### PERFORMANCE

SEATING CAPACITY	2 Person
CURB WEIGHT	1475 lb (669 kg)
BED LOAD CAPACITY	800 lb (363 kg)
VEHICLE LOAD CAPACITY	1200 lb (544 kg)
SPEED	14.5 mph ± .05 mph (23.3 kph ± 0.8 kph)
PROGRAMMABLE SPEED RANGE	5-19 mph (8-30.5 kph)
TOWING CAPACITY	1500 lb (680 kg) max
OUTSIDE CLEARANCE CIRCLE	21.5 ft (6.6 m)

### STEERING & SUSPENSION

STEERING	Self-Compensating Rack and Pinion
FRONT/REAR SUSPENSION	Leaf Springs w/ Hydraulic Shock Absorbers
SERVICE BRAKE	Rear Wheel Mechanical Self-adjusting Drum
PARKING BRAKE	Self-compensating, Single Point Engagement
FRONT/REAR TIRES	18 x 8.5-8

[www.cushman.com](http://www.cushman.com)

©2018 Textron Specialized Vehicles Inc. Features and specifications of the vehicles are subject to change without notice. Vehicle as photographed may include options not included on base model.

60002-G5 (Rev. 04/2018)