

HAULER™TM ELECTRIC OR GAS UTILITY VEHICLE

1200X

13.5 hp Kawasaki® Gas Engine or
48-volt Electric Drivetrain
Limited Slip Differential Option



Features and specifications of the vehicles are subject to change without notice.
Vehicle as photographed may include options not included on base model.



CUSHMAN™



CUSHMAN™
LET'S WORK.™

HAULER 1200X
ELECTRIC AND GAS UTILITY VEHICLE

ELECTRIC

GAS

More than Packs a Punch

Got a job that's dwarfing your to-do list? You need the Cushman Hauler™ 1200X. With a 9.6-cubic-foot cargo bed, lifted suspension and trail tires, this machine will get you there and back in a hurry. Its muscle comes from your choice of a quiet, zero-emissions 48-volt electric drivetrain or a powerful 13.5hp Kawasaki® gas-powered engine. An optional limited-slip differential provides optimal handling and traction on poor terrain without damaging turf. And for the largest sites, the Hauler 1200X can be equipped with an optional 14.9-cubic-foot aluminum cargo bed for additional cargo space. When the job is too big for anything else, give it to the Hauler 1200X.



	ELECTRIC	GAS
	DIMENSIONS	
Overall Length	113.0 in (287 cm)	113.0 in (287 cm)
Overall Width	48.5 in (123 cm)	48.5 in (123 cm)
Overall Height w/o Roof	52.5 in (133 cm)	52.5 in (133 cm)
Overall Height w/ Struts & Roof	77.0 in (196 cm)	77.0 in (196 cm)
Wheel Base	77.0 in (196 cm)	77.0 in (196 cm)
Front Wheel Track	38.0 in (97 cm)	38.0 in (97 cm)
Rear Wheel Track	38.5 in (98 cm)	38.5 in (98 cm)
Ground Clearance	6.0 in (15 cm)	5.3 in (13 cm)
Cargo Box Width (inside)	44 in (112 cm)	44 in (112 cm)
Cargo Box Length (inside)	36 in (91 cm)	36 in (91 cm)
Cargo Box Depth (inside)	10.5 in (27 cm)	10.5 in (27 cm)
Cargo Box Capacity & Material	9.6 cu ft (0.27 m3) / Roto-molded poly	9.6 cu ft (0.27 m3) / Roto-molded poly
	POWER	
Power Source	48V DC	4-Cycle, 24.5 ci (401cc) Cylinder
Motor Type/Valve Train	Shunt Wound	Single Cylinder OHV
Horsepower (kW)	2.5 hp (1.9kW) @ 2700 rpm	13.5 hp (9.7 kW) Exceeds SAE J1940 Std.
Electrical System	48V	Starter/Generator. Solid State Reg.
Batteries (Qty, Type)	Eight, 6V Deep Cycle	One, 12V Maintenance Free
Drive Train	Motor Shaft Direct Drive	Continuously Variable Transmission
Oil Filter	n/a	Spin-On
Cooling System	n/a	Air Cooled
Fuel Capacity	n/a	6.0 Gallon (22.7 L) Tank
Gear Selection	Dash Mount F-N-R Switch	Forward - Reverse
Transaxle	Differential with Helical Gears	Differential with Helical Gears
Rear Axle Ratio	14.7:1	11.42:1(Forward) 15.78:1(Reverse)
	PERFORMANCE	
Seating Capacity & Style	2-Person, Bench	2-Person, Bench
Dry Weight	820 lb (375 kg)	910 lb (415 kg)
Curb Weight	1310 lb (595 kg)	950 lb (435 kg)
Vehicle Load Capacity	1000 lb (450 kg)	800 lb (360 kg)
Outside Clearance Circle	22.0 ft (6.7 m)	22.0 ft (6.7 m)
Speed (level ground)	16 mph +/- 0.5 mph (26 kph +/- 0.8 kph)	17 mph +/- 0.5 mph (27.4 kph +/- 0.8 kph)
Towing Capacity	600 lb (270 kg) max.	500 lb (225 kg) max.
	STEERING & SUSPENSION	
Steering	Self-compensating Rack & Pinion	Self-compensating Rack & Pinion
Front Suspension	Leaf Springs w/ Hydraulic Shock Absorbers	Leaf Springs w/ Hydraulic Shock Absorbers
Rear Suspension	Leaf Springs w/ Hydraulic Shock Absorbers	Leaf Springs w/ Hydraulic Shock Absorbers
Service Brake	Rear wheel mechanical self-adjusting drum	Rear wheel mechanical self-adjusting drum
Parking Brake	Self-compensating, single-point engagement	Self-compensating, single-point engagement
Front & Rear Tires	22x9 - 10 Uni-Directional	22x9 - 10 Uni-Directional
	FRAME & COLOR	
Frame	Powder Coated Welded Steel	Powder Coated Welded Steel
Front Body & Finish	Injection Molded TPO	Injection Molded TPO
Rear Body & Finish	Steel. Base Coat/Clear Coat	Steel. Base Coat/Clear Coat
Standard Color	Patriot Blue	Patriot Blue

Options & Accessories

- Differential Guard
- Locking Glove Box
- Horn
- Windshield
- Canopy
- State of Charge Meter
- Taillights
- Brakelights
- Trailer Dump
- Body Color (Forest Green, Bright White, Yellow, Black or Custom Options)
- Turn Signal with Four-Way Flashers
- Strobe Lights
- Work Lights
- Weather Enclosure
- Steel Cab