

# HAULER™ PRO

ELECTRIC AC  
UTILITY VEHICLE

72-volt AC Electric Drivetrain

1,000-lb Load Capacity

9.6 cu-ft Cargo Box Capacity

**72v**  
ELECTRIC

**1000<sup>lb</sup><sub>MAX</sub>**  
LOAD

**1262<sup>lb</sup><sub>MAX</sub>**  
TOW

**50 MILES**  
PER CHARGE



Features and specifications of the vehicles are subject to change without notice.  
Vehicle as photographed may include options not included on base model.



**CUSHMAN™**



**CUSHMAN™**  
LET'S WORK!

## Fully loaded and ready to work all day long.

Equipped with a 72-volt AC drivetrain, the Cushman® Hauler™ PRO has the range, power and operational efficiencies your course demands. Powered by a quiet, zero emissions 72-volt electric drivetrain, the Hauler PRO features a daily range of up to 50 miles fully loaded and all the energy benefits of a low maintenance AC system. A standard on-board charger gives you the flexibility to charge the Hauler PRO at any outlet within your facility. With a 1000-pound vehicle payload, optional limited-slip differential the Hauler PRO is the strong silent type, that is easy to work with!



## HAULER PRO ELECTRIC AC UTILITY VEHICLE

DIMENSIONS	
Overall Length	111 in (281 cm)
Overall Width	49.8 in (126 cm)
Overall Height w/o Roof	47.5 in (121 cm) (Top of steering wheel)
Overall Height w/ Struts & Roof	70.8 in (180 cm)
Wheel Base	75.3 in (191 cm)
Front Wheel Track	37.0 in (94 cm)
Rear Wheel Track	38.8 in (99 cm)
Ground Clearance	5.5 in (14 cm)
Cargo Box Width (inside)	44.0 in (112 cm)
Cargo Box Length (inside)	36.0 in (91 cm)
Cargo Box Depth (inside)	10.5 in (27 cm)
Cargo Box Capacity & Material	9.6 cu ft (0.27 m <sup>3</sup> ) / Roto-molded polyethylene
POWER	
Power Source	72-Volts DC
Motor Type	AC Induction
Horsepower (kW)	22.4HP (16.7 kW) - Measured at Peak Torque
Electrical System	72 Volt
Batteries (Qty, Type)	Nine, 8-Volt Deep Cycle
Drive Train	Motor Shaft Direct Drive
Battery Charger	900 Watt 72V DC
Speed Controller	350 Amp AC
Gear Selection	Seatwrap Mount Forward-Neutral-Reverse Switch
Transaxle	Differential with Helical Gears
Rear Axle Ratio	17:1
PERFORMANCE	
Seating Capacity & Style	2-Person, Bench
Dry Weight	804 lb (365 kg) (Without Batteries)
Curb Weight (w/ Batteries)	1371 lb (622 kg)
Bed Load Capacity	600 lb (270 kg)
Vehicle Load Capacity	1000 lb (450 kg)
Outside Clearance Circle	22.1 ft (6.7 m)
Speed (level ground)	13 mph +/- 0.5 mph (21 kph +/- 0.8 kph)
Programmable Speed Range	5 - 19 mph (8 - 30.5 kph)
Towing Capacity	1262 lb (5,614 N) Max Drawbar
STEERING & SUSPENSION	
Steering	Self-compensating Rack & Pinion
Front Suspension	Leaf Springs w/ Hydraulic Shock Absorbers
Rear Suspension	Leaf Springs w/ Hydraulic Shock Absorbers
Service Brake	Rear Wheel Mechanical Self-adjusting Drum
Parking Brake	Self-compensating, Single Point Engagement
Front Tires	20 x 8 - 10 (4 Ply Rated)
Rear Tires	20 x 8 - 10 (4 Ply Rated)
FRAME & COLOR	
Frame	Durashield™ Powder Coated Welded Steel
Front Body & Finish	Injection Molded TPO
Rear Body & Finish	Steel. Base Coat/Clear Coat
Standard Color	Forest Green

### Factory Installed Options & Field Accessories

- Limited Slip Differential
- Locking Glove Box
- Windshield
- Roof
- Taillights
- Brake Lights
- Trailer Dump (Steel and Poly)
- 14.9 cu ft aluminum cargo bed
- 12 Volt Outlet
- Body Color (Patriot Blue, Ivory, White, Yellow, Orange or Custom Options)
- Turn Signal with Four-Way Flashers
- Strobe Lights
- Work Lights
- Weather Enclosure
- Defroster/Fan
- Steel Cab
- Beacon