

# E-Z-GO® Express® L6

# LET THE GOOD TIMES GROW.

It's time to get away, time to explore and see what adventures you can find along the next path. With eco-friendly powertrain options, rugged tires, and higher ground clearance, the Express L6 gives you a smooth, stylish ride. The 72-volt Express L6 offers exclusive technology which boasts a longer battery life, so you'll spend more time on the go with your friends and family. Hop into the Express L6 to see where the day can take you.





DIMENSIONS	ELECTRIC	GAS
Overall Length	143.5 in (364 cm)	143.5 in (364 cm)
Overall Width	49.0 in (125 cm)	49.0 in (125 cm)
Overall Height (w/o roof)	52.5 in (133 cm)	53.5 in (136 cm)
Overall Height (w/ roof)	77.5 in (197 cm)	78.5 in (200 cm)
Wheel Base	96.5 in (245 cm)	94.5 in (240 cm)
Front Wheel Track	38.5 in (98 cm)	38.5 in (98 cm)
Rear Wheel Track	39.0 in (99 cm)	39.0 in (99 cm)
Ground Clearance  @ Differential	7.0 in (18 cm)	6.0 in (15 cm)
POWER		
Power Source	72 Volt AC	4-Cycle 24.5 cu in (401cc) Low-Emissions
Valve Train	N/A	Single Cylinder OHV
	AC Induction	N/A
Motor Type		13.5 hp (10.1 kW) Exceeds SAE J1940 Std
Horsepower (kW)	22.4 HP (16.7 kW) 72 Volt	
Electrical System		Starter/Generator — Solid State Regulator
Batteries (qty/type)	Six, 12 Volt deep cycle	One, 12 Volt Maintenance Free
Key or Pedal Start	Pedal start	Pedal
Air Cleaner	N/A	Replaceable Dry Cartridge
Lubrication	N/A	Pressurized Oil System
Oil Filter	N/A	Spin-On
Cooling System	N/A	Air Cooled
Fuel Capacity	N/A	5.8 Gallon (22 L)
Battery Charger	72 V DC Delta Q, 120/230 VAC, UL & CSA	N/A
Speed Controller	350 Amp AC	N/A
Drivetrain	Motor Shaft Direct Drive	Continuously Variable Transmission (CVT)
Transaxle	Differential with Helical Gears	Differential with Helical Gears
Direction Selector	Dash mounted FNR	Forward-Reverse
Rear Axle Ratio	17:1	11.42:1 (Forward) 15.78:1 (Reverse)
PERFORMANCE		
Seating Capacity	6-passenger	6-passenger (4-passenger with Optional Cargo Bed)
Dry Weight (w/o batteries)	964 lbs. (437 kg)	1063 lbs. (482 kg)
Curb Weight	1560 lbs. (708 kg)	1110 lbs. (504 kg)
Vehicle Load Capacity	1200 lbs. (544 kg)	1200 lbs. (544 kg)
Outside Clearance Circle	25.5 ft (7.8m)	25.5 ft (7.8m)
High Speed (level ground)	16.5 mph ± 0.5 mph (26 kph ± 0.8 kph)	16.5 mph ± 0.5 mph (26 kph ± 0.8 kph)
Low Speed (level ground)	12 mph ± 0.5 mph (19.3 kph ± 0.8 kph)	12 mph ± 0.5 mph (19.3 kph ± 0.8 kph)
STEERING & SUSPENSION		
Steering	Self-Compensating Rack and Pinion	Self-Compensating Rack and Pinion
Suspension	Leaf Springs with Hydraulic Shock Absorbers	Leaf Springs with Hydraulic Shock Absorbers
Service Brake	Rear Wheel Mechanical Self-Adjusting Drum	Rear Wheel Mechanical Self-Adjusting Drum
Parking Brake	Self-Compensating, Single Point Engagement	Self-Compensating, Single Point Engagement
Tires	Desert Eagle 23 x 10 - 14 on Alloy Wheel	Desert Eagle 23 x 10 - 14 on Alloy Wheel
BODY & CHASSIS		
Frame	Welded Steel with DuraShield™ Powder Coat	Welded Steel with Powder-Coat Protection
Body & Finish	Injection Molded TPO	Injection Molded TPO
Available Body Colors	Almond, Black, Burgundy, Electric Blue, Flame Red, Forest Green, Inferno Red, Ivory, Metallic Charcoal, Patriot Blue, Platinum, White,	Almond, Black, Burgundy, Electric Blue, Flame Red, Forest Green, Inferno Red, Ivory, Metallic Charcoal, Patriot Blue, Platinum, White,
Available Seat Colors	Jacobsen Orange  Tan, Oyster, Black, Gray on Black, Red on Black, White on Blue, White on Red	Jacobsen Orange  Tan, Oyster, Black, Gray on Black, Red on Black, White on Blue, White on Red



# **STANDARD FEATURES EXPRESS L6 ELECTRIC**

- 23-in all-terrain tires
- 72-volt AC powertrain
- Rabbit/Turtle speed switch
- Fold-down windshield

### **EXPRESS L6 GAS**

- 23-in all-terrain tires
- 82-in Top

- · Low oil indicator
- Fuel gauge

### **POPULAR OPTIONS & ACCESSORIES**

- Fold-down windshield

- (replaces rear-facing seat)
- Roto-molded plastic bed
- Comfort grip steering wheel
- Turn signals w/ 4-way flashers
- Hour meter
- Limited slip differential

- 12-volt accessory outlet (gas only)



Enquiries: dan@qldgolfcarts.com.au



07 5455 5328 | 0488 557 684



