



CUSHMAN®

HAULER® PRO-X



GET MORE MILEAGE OUT OF EVERY WORK DAY.

Stand back and let the new Hauler® PRO-X raise your expectations on what a 72-volt AC powertrain can do. With its 50-mile range, silent operation and lifted suspension, the Hauler PRO-X will help you and your team work seamlessly without disrupting your environment. Outstanding energy efficiency, low operational costs and a dash that easily accommodates radios, clip boards, oversized beverage containers and more, the Hauler PRO-X is equipped for action.

LET'S WORK.®

72V
AC
ELECTRIC

1200LB
TOW
CAPACITY

12 CU FT
CARGO
BED

900LB
LOAD
CAPACITY



CUSHMAN® HAULER® PRO-X



HIGHER GROUND CLEARANCE



STANDARD ON BOARD CHARGER



ROTO-MOLDED BED



VERSATILE DASH STORAGE

OPTIONS & ACCESSORIES

- Bed Dividers
- Long-Handled Tool Holder
- Cargo Mesh Netting
- L-Track Aluminum Bed System
- Weather Enclosure
- USB Outlet
- 12-Volt Outlet
- Canopy Storage Net
- Brush Guard
- Rearview Mirror
- ROPS-Certified Cab
- Ladder/Hoop Rack
- Brake Lights
- Tail Lights
- 20" Improved surface tires
- E-Shield™ Frame
- Premium Steering Wheel



COVERED WITH THE 2-YEAR CUSHMAN CARE TOTAL PROTECTION WARRANTY

BODY & CHASSIS

| | |
|----------------|---|
| FRAME | Welded Steel with DuraShield™ Powder Coat |
| BODY & FINISH | Injection Molded TPO |
| STANDARD COLOR | Patriot Blue |

DIMENSIONS

| | |
|--------------------------|---------------------------------|
| OVERALL LENGTH | 119 in (302.3 cm) |
| OVERALL WIDTH | 49.4 in (125.5 cm) |
| OVERALL HEIGHT W/ CANOPY | 77 in (195.6 cm) |
| WHEEL BASE | 77.5 in (196.9 cm) |
| FRONT WHEEL TRACK | 38.0 in (96.5 cm) |
| REAR WHEEL TRACK | 38.0 in (97.8 cm) |
| GROUND CLEARANCE | 7.2 in (18.29 cm) |
| CARGO BOX CAPACITY | 12 cu ft (.034 m ³) |

POWER

| | |
|--------------------|--|
| POWER SOURCE | 72-Volts |
| MOTOR TYPE | AC Induction |
| HORSEPOWER (KW) | 22.4HP (16.7 kW) - Measured at Peak Torque |
| ELECTRICAL SYSTEM | 72 Volt |
| BATTERY (QTY/TYPE) | Nine 8-Volt Deep Cycle |
| BATTERY CHARGER | 900 Watt 72V DC |
| KEY OR PEDAL START | Pedal |
| DRIVE TRAIN | Motor Shaft Direct Drive |
| TRANSAXLE | Differential with Helical Gears |
| SPEED CONTROLLER | 350 Amp AC |
| GEAR SELECTION | Forward-Neutral-Reverse |
| REAR AXLE RATIO | 17:1 |

PERFORMANCE

| | |
|--------------------------|---|
| SEATING CAPACITY | 2 Person |
| CURB WEIGHT | 1513 lb (686 kg) |
| BED LOAD CAPACITY | 500 lb (227 kg) |
| VEHICLE LOAD CAPACITY | 900 lb (408 kg) |
| SPEED | 16.5 mph ± 0.5 mph (26.6 kph ± 0.8 kph) |
| TOWING CAPACITY | 1200 lb (544 kg) max |
| OUTSIDE CLEARANCE CIRCLE | 23.5 ft (7.2 m) |

STEERING & SUSPENSION

| | |
|-----------------------|--|
| STEERING | Self-Compensating Rack and Pinion |
| FRONT/REAR SUSPENSION | Leaf Springs w/ Hydraulic Shock Absorbers |
| SERVICE BRAKE | Rear Wheel Mechanical Self-adjusting Drum |
| PARKING BRAKE | Self-compensating, Single Point Engagement |
| FRONT/REAR TIRES | 20 x 8.00 -10 |

QLD GOLF CARTS

UNITS 1 - 3 / 15 RENE STREET
NOOSAVILLE QLD 4566



dan@qldgolfcarts.com.au

07 5455 5328 | 0488 557 684

www.cushman.com

©2016 Textron Specialized Vehicles Inc. All rights reserved. Features and specifications of the vehicles are subject to change without notice. Vehicle as photographed may include options not included on base model.

60007-G4 (Rev. 06/2016)