



CUSHMAN®



HAULER® 800 ELiTE SERIES

UNRIVALED PERFORMANCE

Cushman® Hauler® 800 ELiTE vehicles are activated by Samsung SDI lithium technology to power through your toughest work days. With faster charge times, consistent performance and increased range, the Hauler 800 ELiTE series will maximize the productivity of your crew and decrease energy costs. With a fully customizable cargo bed, highly functional dash and a broad range of accessories, Hauler 800 ELiTE vehicles have everything you need to finish job after job.

LET'S WORK.®

ELiTE

48V AC
LITHIUM

UP TO
800LB
PAY LOAD

5-YEAR
BATTERY WARRANTY

ZERO
MAINTENANCE
BATTERIES



Hauler® 800 ELITE



Hauler® 800X ELITE

CUSHMAN® HAULER® 800 ELITE SERIES



BED DIVIDERS



HIGHLY FUNCTIONAL DASH



OPTIONAL BALL CAGE



OPTIONAL FLOOR MOUNT

OPTIONS & ACCESSORIES

- Limited Slip Differential
- 4-Wheel Mechanical Brakes
- Locking Glove Box
- Glove Box Mat
- Floor Mount Attachment
- Windshield
- Canopy
- Power Dump
- Long Handled Tool Holders
- Radio Holder
- Interior Tool Hook
- LED Headlights - Hi/Low
- Taillights
- Brakelights
- Comfort Grip Steering Wheel
- Rearview Mirror
- 12-volt Outlet
- USB Port
- Unique Key Switch
- Hour Meter
- Side Body Color
- Weather Enclosure
- Cab
- Ball Cage
- ROPS
- Hubcaps
- Ball Hitch Receiver

HAULER 800 ELITE

HAULER 800X ELITE

BODY & CHASSIS		
FRAME	Welded steel with E-Shield ecoat plus DuraShield™ powder coat	
BODY & FINISH	Injection Molded TPO (front), Injection Molded PP (rear)	
STANDARD COLOR	Forest Green or Patriot Blue	
DIMENSIONS		
OVERALL LENGTH	110 in (280 cm)	110 in (280 cm)
OVERALL WIDTH	49 in (125 cm)	49 in (125 cm)
OVERALL HEIGHT	47 in (120 cm)	51 in (130 cm)
WHEEL BASE	65.5 in (166 cm)	65.5 in (166 cm)
FRONT WHEEL TRACK	37.0 in (94 cm)	37.0 in (94 cm)
REAR WHEEL TRACK	38.0 in (97 cm)	38.0 in (97 cm)
GROUND CLEARANCE	4.3 in (11 cm)	5.5 in (14 cm)
CARGO BOX CAPACITY	8.4 cu ft (0.24 m3)	8.4 cu ft (0.24 m3)
POWER		
POWERTRAIN	48-Volt AC Drive	
VALVE TRAIN	N/A	
HORSEPOWER (KW)	11.7 HP (8.7 kW) Peak	
ELECTRICAL SYSTEM	48-Volt	
BATTERY (QTY/TYPER)	Two Lithium Ion 48 Volt	
KEY OR PEDAL START	Pedal	
OIL FILTER	n/a	
COOLING SYSTEM	n/a	
FUEL CAPACITY	n/a	
DRIVE TRAIN	Motor Shaft Direct Drive	
TRANSAXLE	Differential with Helical Gears	
GEAR SELECTION	Dash Mount Forward-Neutral-Reverse	
REAR AXLE RATIO	16.99:1	
PERFORMANCE		
SEATING CAPACITY	2-Person	
CURB WEIGHT	803 lb (364 kg)	797 lb (361 kg)
BED LOAD CAPACITY	400 lb (181 kg)	325 lb (147.4 kg)
VEHICLE LOAD CAPACITY	800 lb (360 kg)	725 lb (328 kg)
SPEED	14.5 +/-0.5 mph (23.3 +/- 0.8 kph)	16.5 mph ± 0.5 mph (26.5 kph ± 0.8 kph)
TOWING CAPACITY	900 lb (408 kg)	500 lb (230 kg)
OUTSIDE CLEARANCE CIRCLE	18.9 ft (5.8 m)	
STEERING & SUSPENSION		
STEERING	Self-Compensating Rack & Pinion	
SUSPENSION	Leaf Springs w/ Hydraulic Shock Absorbers	
SERVICE BRAKE	Rear Wheel Mechanical, Self-Adjusting Drum	
PARKING BRAKE	Self-Compensating, Single-Point Engagement	
TIRES (FRONT & REAR)	20 x 8-10 (6 Ply Rated)	